

DLT-18HD LED Light Tower

metrolite



The DLT-18HD LED light tower delivers light and power in a functional and sleek design.

Features:

- 30% Load Bank/Load Leveler
- Deep Sea Electronics with GPS and telematics capabilities
- LED interior compartment work lights
- 110% secondary fluid containment
- Cold weather package
- 4 high output 320-watt LED lamps
- Powder coated steel exterior
- Heavy duty, hydraulic activated galvanized steel mast
- Automatic On at Dusk, Off at Dawn feature
- Reversible pintle hitch / ball hitch
- 4 outriggers for superior wind stability
- Kohler engine



Call (844) 732 9466
www.axiomequipmentgroup.com

DLT-18HD LED Light Tower

metrolite

The DLT-18HD light tower effectively and efficiently illuminates your jobsite, 24 hours per day.

The rugged, dependable design of the DLT-18HD light tower means it can withstand extreme temperatures and variable weather while consistently delivering effective, efficient light and reliable power.

The low fuel consumption of this light tower provides savings of up to 45 litres per day, compared to a traditional 20kW diesel light tower.

FEATURES:

- 30% Load Bank/Load Leveler
- Automatic Dusk-to-Dawn sensor with programmable automatic start and stop to suit your schedule
- Large 240-litre fuel tank to reduce labour costs of refueling
- Over 60 hours of runtime at prime load
- Interior compartment work lights so you can work safely and efficiently at all times
- Heavy duty, galvanized steel mast is hydraulic activated.
- Powder coated steel enclosure is insulated and fully sound attenuated
- 110% secondary fluid containment
- DSE interface for remote operation of the DLT-18HD, including engine operation and fuel level monitoring and GPS positioning. Ideal for remote applications and large jobsites.
- Fork pockets and single point lift for rigging
- Naturally aspirated Kohler diesel engine for continuous, reliable power
- Auxiliary power outlets

SPECIFICATIONS

SPECIFICATIONS			DLT-18HD
Floodlights			4 x 320 W LED
Total Lumen			166,200
L x W x H	in		122 x 57.5 x 95
Total Weight	lbs		2645
Mast Height	m (ft)		8.5 (27.8)
Max Wind Rating	kph (mph)		110 (68)
Power	kW (kVA)		15 (18)
Electrical Receptacles			(4) 20 Amp/120V GFI Duplex (2) 30 Amp Twist Lock (1) 50 Amp Twist Lock
Interior Compartment Work Lights			2x LED
Generator End			Linz SLS18 MD
Engine Model			Kohler KDI 1903 M
Sound Level	dba		68
Fuel			Diesel
Fuel Tank Capacity	litres / US gallons		250 / 66
Fuel Consumption	litres per hour		2.8L at 50% load 4.0L at 75% load 5.4L at 100% load
Run Time (75% Load)	hr		62.5
Secondary Fluid Containment			110%



Call (844) 732 9466
www.axiomequipmentgroup.com