

metrolite

# Diesel LED Light Tower



**DLT C-Series 4kW & 8kW**

**COLD WEATHER PACKAGE**

The **DLT C-Series** light towers are designed to be reliable and tough in any environment while consistently delivering efficient power and effective lighting to your jobsite.

The low fuel consumption of the DLT C-Series provides considerable savings compared to traditional 6 and 8kW light towers.

#### Features:

- Efficient LED Lamps
- Deep Sea Electronics controller
- Fork pockets and single point lift
- Automatic dawn to dusk sensor
- Extended service intervals of 750 hours between oil changes
- Electrical receptacles to provide power to other tools on site

Specifications	DLT-4C+	DLT-8C
L x W x H	63 in x 55 in x 92.5 in	97 in x 56.5 in x 91 in
Total Weight w/o Fuel	1,316 lbs	1907 lbs
Floodlights	4 x 320 W LED	4 x 350 W LED
Total Lumen	166,200 lm	189,000 lm
Mast Height	23 ft (7 m)	23 ft (7m)
Max Wind Rating	100 kph (62 mph)	100 kph (62 mph)
Power	4.2 kW	8 kVA / 6.4 kW
Electrical Receptacles	1 x 115V15A Outlet 1 x 115V15A Inlet	2 x 20A GFCI outlet 1 x 30A twist lock outlet 1 x 30A twist lock inlet
Generator End	Linz	Linz / NSM
Engine	Kohler KDW702	Mitsubishi L3E
Sound Level	65 dB(A) at 7 meters	60 dB(A) at 7 meters
Fuel	Diesel	Diesel
Fuel Tank Capacity	120 L (32 US gal)	170 L (45 US gal)
Fuel Consumption (lights only)	0.55 L/hr (0.15 gal/hr)	1.1 L/hr (0.29 gal/hr)
Run Time (lights only)	218 hrs	152 hrs
Secondary Fluid Containment	110%	110%

All specifications are subject to change without prior notice.

**AXIOM**  
EQUIPMENT GROUP  
EXPECT HIGHER STANDARDS ON SITE

**Call (844) 732 9466**  
[www.axiomequipmentgroup.com](http://www.axiomequipmentgroup.com)