

The **megatank**, built robustly with innovative features, is the perfect solution for safe and secure transport and storage of industrial lubricants and hazardous liquids worldwide. With options from 1000L to 3000L tanks, the **megatank** is ready to meet your fuel storage needs!

The range has an extra large equipment compartment area that can house a variety of optional accessories:

- Digital flow meters
- 120V and 12V pump kits
- Feed & return lines
- Retractable Hose Reels
- Water particulate filters

Approvals and Certifications

- ✓ UN31A/Y Compliant Design (Transport Canada / US DOT)
- ✓ ULC S601 Compliant Design (Canada)
- ✓ UL142 Compliant Design (USA)
- ✓ Pressure Tested

Features:

- Bi-directional fork pockets and lifting brackets for easy maneuverability
- Stackable 2 high when full and 3 high when empty
- Internal baffle plates for protection against sloshing when transporting
- The three-tier component design allows the inner tank to be completely removed and disconnected to allow for easy cleaning and maintenance.
- Primary hatch lid opens to a conveniently positioned component ports plate with access to an extra-large equipment compartment area
- Spacious equipment chamber with a universal bracket system inside that can support retractable hose reels, along with a variety of pump kits.
- Multiple ports that can connect up to three pieces of machinery at one time and allow dispensing simultaneously.
- Galvanized stocking corner doubles up as a lifting bracket.

SPECIFICATIONS		MT1000	MT2000	MT3000
Capacity	gal (L)	242 (916)	523 (1980)	795 (3008)
Safe Fuel Fill Level	gal (L)	230 (870)	497 (1881)	755 (2858)
Dimensions (L × W × H)	in (mm)	58.47 × 45.28 × 50.98 (1485 × 1150 × 1295)	90.55 × 52.17 × 50.98 (2300 × 1325 × 1295)	90.55 × 74.22 × 50.98 (2300 × 1885 × 1295)
Outer Tank Thickness	mm (gauge)	3 (11)	3 (11)	3 (11)
Inner Tank Thickness	mm (gauge)	3 (11)	3 (11)	3 (11)
Weight (Empty)	lbs (kg)	1065 (483)	1612 (731)	2083 (945)
Weight (Full)	lbs (kg)	3045 (1381)	5889 (2671)	8583 (3893)

All specifications are subject to change without prior notice.



Call (866) 921 5616 www.axiomequipmentgroup.com